

# Online Vibration Monitoring of Track Grinding Machine

Prof. H. P. Chaudhari<sup>1</sup>, S. M. Nimbalkar<sup>2</sup>, Nikita N. Chaudhari<sup>3</sup>, Harshali Narkhede<sup>3</sup>

<sup>1</sup>HOD, Instrumentation, AISSMS's IOIT, Pune, Maharashtra, India

<sup>2</sup>Deputy Manager, S.K.F. Pvt. Ltd., Pune, Maharashtra, India

<sup>3</sup>Instrumentation, AISSMS's IOIT, Pune, Maharashtra, India

## ABSTRACT

In modern industry, process must be flexible. To increase reliability and quality of the product at low cost, machine tools must work without any failure. To avoid unplanned downtime due to sudden failure of spindles, In order to achieve this goal, condition monitoring is very essential. This paper focuses on the condition monitoring of machine tool elements. Changes in the machine conditions (vibrations) are detected automatically in real time by using online vibration monitoring system. Vibration measurement sensor (accelerometers) is used to sense the vibration of a machine in this project. Accelerometer sensor, SKF vibration monitoring device. GSM modem, HMI etc. have been successfully used in this project.

**Keywords :** Condition Monitoring, Vibration, Machine Tool Element.

## I. INTRODUCTION

Accelerometer is used in this project to measure the vibrations.

### 1.1 Study of grinding machine

A grinding machine is a machine tool used for grinding. It is a process used to finish work pieces (bearing) that must show high accuracy and high surface quality. During the operation, various faults may arise. These failures directly affect the production line which in turn leads to the damage of finished product. To avoid such losses or fault conditions, monitoring proves to be very effective to detect faults at early stages.

### 1.2 Vibration sensor

In order to measure the vibrations of spindle and motor, accelerometer sensor is used. Accelerometer sensor is mounted on a motor and dresser arm of a grinding machine to measure the vibrations. It works on the piezoelectric principle which states that the ability of a material to generate an electric charge in response to applied mechanical stress. CMSS-2100

### 1.3 Overview of SKF vibration monitoring device.

It is a 8-channel condition monitoring device. IMX-8 forms a flexible on-line condition monitoring system tool for rotating machinery applications. It is designed for continuous analysis and monitoring especially where offline monitoring is not practical. It is installed where temperature or vibration does not have adverse effect on it. In conjunction with @aptitude analyst software online vibration readings can be viewed on the mobile phones. With its special Bluetooth feature mobile phones can be connected to it for data analysis.

### 1.4 Overview of HMI

It is a software application that presents information to an operator or user about the state of a process, and to accept and implement the operators control instructions. Typically information is displayed in a graph form of trends. An HMI is often a part of

SCADA. The software used to design the screens of HMI is GT designer-3. HMI used in this project is of Make: Mitshubishi Electric, Model: GS2107-WT80.

### 1.5 Overview of GSM modem

A GSM modem is a modem which accepts a sim card, and operates over a subscription to mobile operators. D-link GSM modem is used in this project.

### 1.6 BLOCK DIAGRAM




Figure 1

### 1.7 Objective of the proposed work

The main objective of the proposed work is to monitor the vibrations of a machine tool by using online monitoring system to improve the productivity and reliability of rotating equipment.

## II. CONCLUSION

Early recognition of spindle vibrations avoiding unplanned downtime. Provision of alert and danger alarms due to which spare spindle can be arranged in advance before failure

## III. ACKNOWLEDGEMENT

Inspiration and guidance are invaluable in every aspect of the life, especially in the field of the academics, which we have received from our respected project guide **Mr.H.P.CHAUDHARI, Head of department (AISSMS IOIT, Pune)**. We would like to thank as he was responsible for the complete project and also for his endless contributions of time, efforts, valuable guidance and encouragement he has given to us. We would also like to thank Principal **Dr.**

**P.B. Mane** without whom we would not have opportunity to reach up to this level and specially mention all the help extended by him, constant inspiration and encouragement to make my project a memorable experience. We are thankful to all the teachers and professors of our department for sharing with us, valuable knowledge of their respective fields. We would also thank our colleagues and friends for their inspiration and motivation and those who helped us directly or indirectly for our project work. We would also thank to library staff and laboratory staff for a cordial support and necessary facilities, which were of great help for preparing this report.

## IV. REFERENCES

- [1]. Yonghuihu, yang yan fellow, IEEE, LijuanWang, andXiangchenQian"IEEE sensor journal", Vol16, No: 10, May 2016.
- [2]. Julian Turner,"Effects of Data Centre Vibration on Compute System Performances",
- [3]. Thomas.I.PaezConsulting, Durango Colorodo,"Sound and Vibration Journal", 2012.
- [4]. G.S.Yadava, S.Saravaman, P.V.Rao,"International Journal of Advanced Technology"July 2006